

SERIES 33



80 Shore A



0°C to +40°C



30 - 50mm



10 - 30kg

Rubber ball wheels

- Black rubber ball wheel
- Zinc plated pressed steel castor housing
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22881:2004



Available Bore Types



Plain
Bore

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Suitable for indoor applications, without aggressive chemicals. They can be used on fragile flooring and carpet.


Industries




Furniture

Floor Suitability


Suitable on tiles and delicate flooring; not recommended on abrasive, unpaved floors or in presence of processing residues. Not recommended in presence of obstacles.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

SERIES 33 CONTINUED



80 Shore A



0°C to +40°C



30 - 50mm



10 - 30kg

TOP PLATE CASTORS



								SWIVEL
30		48	40x40	27x27	5	10	0.11	334101
40		59	40x40	27x27	5	20	0.15	334102
50		69	47x47	35x35	6	30	0.23	334103

BOLT HOLE CASTORS



							BOLT HOLE
30		46	32	9	10	0.09	333101
40		57	32	10	20	0.13	333102
50		66	36	10	30	0.2	333103

BOLT HOLE CASTORS WITH THREADED STEM



								BOLT HOLE
30		51	M8	15	Spanner 13	10	0.1	336101
40		63	M8	15	Spanner 13	20	0.14	336102
50		73	M8	15	Spanner 13	30	0.22	336103

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk