

SERIES 35



80 Shore A



0°C to +40°C



45 - 65mm



20 - 40kg

Rubber half-ball wheels

- Black rubber spherical wheels
- Chrome plated castor housing and electrolytically galvanised Zamak alloy fittings
- Wheels are supplied fully assembled (available in left or right hand versions)
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22881:2004



Available Bore Types



Plain
Bore

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Suitable for indoor applications, without aggressive chemicals. They can be used on fragile flooring and carpet.


Industries




Furniture

Floor Suitability


Suitable on tiles and delicate flooring; not recommended on abrasive, unpaved floors or in presence of processing residues. Not recommended in presence of obstacles.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

SERIES 35 CONTINUED



80 Shore A



0°C to +40°C



45 - 65mm



20 - 40kg

TOP PLATE CASTORS



								RIGHT HAND SWIVEL		LEFT HAND SWIVEL
45			28x28	19x19	5	20	0.09	354101	0.09	354201
55			38x38	27x27	5	30	0.14	354102	0.14	354202
65			38x38	27x27	5	40	0.19	354103	0.19	354203

BOLT HOLE CASTORS WITH THREADED STEM



								RIGHT HAND BOLT HOLE		LEFT HAND BOLT HOLE
45			M8	15	Spanner 12	20	0.09	356101	0.09	356201
55			M8	15	Spanner 12	30	0.13	356102	0.13	356202
65			M10	15	Spanner 12	40	0.18	356103	0.18	356203

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk