

SERIES 51



80 Shore A



-5°C to +40°C



80 - 250mm



30 - 120kg

Black thermoplastic rubber wheel with polypropylene centre

- Hub with plain bore that directly houses the axle
- Zinc plated pressed steel castor housings
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22881:2004



Available Bore Types



Plain Bore

Environments of Use


- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses


Mainly suitable for static applications, on even flooring and for light carrying capacities.

Floor Suitability


Suitable on tiles and resin-cement; not recommended on abrasive, unpaved floors or in presence of processing residues. Not suitable for uneven surfaces.



Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

SERIES 51 CONTINUED



80 Shore A



-5°C to +40°C



80 - 250mm










30 - 120kg

WHEELS












Plain Bore

 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (kg)	 (code)
80	26	10	34	30	0.09	511101
100	30	8	35	35	0.11	511112
100	30	12	35	35	0.11	511122
125	35	15	44	50	0.18	511103
150	35	15	44	90	0.23	511104
175	45	20	59	100	0.33	511105
200	50	20	59	120	0.72	511106
250	50	20	59	120	0.89	511108










INSTITUTIONAL TOP PLATE CASTORS



							 (daN)	 (kg)	SWIVEL
80	26	106	60x60	45x45	6	28	30	0.43	514411
100	30	128	60x60	45x45	6	32	35	0.48	514412











INSTITUTIONAL BOLT HOLE CASTORS WITH THREADED STEM



							 (daN)	 (kg)	BOLT HOLE
80	26	103	M12	25	41	28	30	0.35	516801
100	30	126	M12	25	41	32	35	0.40	516802

STANDARD DUTY CASTORS - NL



							 (daN)	 (kg)	SWIVEL	 (kg)	FIXED
80	26	107	100x85	80x60	9	37	30	0.62	514401	0.34	515701
100	30	128	100x85	80x60	9	35	35	0.63	514402	0.37	515702
125	35	156	100x85	80x60	9	37	50	0.82	514403	0.48	515703
150	35	182	100x85	80x60	9	42	90	0.91	514404	0.54	515704

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk