

SERIES 53AS



80 Shore A



-20°C to +60°C



80 - 200mm



65 - 230kg

Conductive black rubber tyre

- Standard duty loads
- Zinc plated pressed steel castor housings
- Conductive wheel has an earthing resistance below 0.1m ohm in accordance with ISO 22878:2004
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22883:2004



Available Bore Types



Roller Bearing

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Suitable for trolleys with light-duty loads, also in the presence of obstacles and for indoor-outdoor use.


Industries




Waste & Recycling

Floor Suitability


Suitable for all types of floors, even outdoors. They easily overcome obstacles, do not damage fragile floors, but they may mark the floor.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 53AS CONTINUED



80 Shore A



-20° C to +60° C



80 - 200mm












65 - 230kg

ANTI-STATIC OPTION

Conductive wheel has earthing resistance in accordance with ISO 22878:2004



 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (daN)	 (daN)	 (kg)	 (code)
80	25	12	34	260	60	65	0.19	533101AS
100	30	12	34	300	75	80	0.31	533102AS
125	37.5	15	44	330	85	130	0.54	533103AS
140	37.5	15	44	340	95	150	0.66	533104AS
180	45	20	58	390	130	200	1.39	533105AS
200	50	20	58	410	140	230	1.81	533106AS
225	50	20	58	420	160	250	2.42	533107AS
250	60	25	73	500	175	300	3.14	533108AS
280	60	25	73	550	200	390	3.84	533109AS
160	40	20	58	370	120	180	1.07	533110AS
150	40	15	44	350	100	170	0.76	533111AS
200	50	25	58	410	140	230	1.78	533206AS