

SERIES 60WA



95 Shore A



-15°C to +80°C



80 - 250mm



150 - 700kg

Polyurethane tyre with special wrap around design, bonded to polyamide 6 centre, ball bearing

- High load capacity
- Low abrasion, non-marking
- Excellent chemical resistance
- Low rolling resistance
- Offers quieter running and higher carrying capacity than wheels of equivalent nature



Available Bore Types



Ball Bearing

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Suitable for trolleys and machinery with medium-heavy duty loads, also in case of continuous handling. The ball bearing model is excellent for manual-mechanical handling and speed up to 6km/h. Suitable for indoor and outdoor use with frequent washing and sterilisation.

Industries



Clean Room Laboratories



Food Industry




Automotive




Airport/Aerospace

Floor Suitability


Suitable for tiles and cement-resin. Not recommended for unpaved floors or in presence of processing residues. Not suitable in presence of obstacles, even if small. They do not mark or damage fragile floors.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 60WA CONTINUED



95 Shore A



-15°C to +80°C



80 - 250mm









150 - 700kg

BLUE POLYURETHANE TYRE 95 SHORE A









Ball
Bearing

 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
80	35	12	40	150	60WA2101
100	35	12	40	200	60WA2102
125	45	15	50	250	60WA2103
150	45	20	60	380	60WA2104
160	45	20	60	400	60WA2105
200	50	20	60	500	60WA2106
250	60	25	75	700	60WA2107

PURPLE ELASTIC POLYURETHANE TYRE 80 SHORE A









Ball
Bearing

 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
80	35	12	40	130	61WA2101
100	35	12	40	180	61WA2102
125	40	15	50	200	61WA2103
150	45	20	60	200	61WA2104
160	45	20	60	300	61WA2105
200	48	20	60	450	61WA2106

GREY TPR TYRE 85 SHORE A



Ball
Bearing

 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
80	35	12	40	120	71WA2101
100	35	12	40	150	71WA2102
125	40	15	50	200	71WA2103
150	45	20	60	260	71WA2104
160	45	20	60	260	71WA2105
200	50	20	60	350	71WA2106
250	60	25	75	450	71WA2107