

SERIES 60WAS



95 Shore A



-20° C to +70° C



80 - 200mm



150 - 500kg

Hard wrap around, conductive, polyurethane tyre, bonded to nylon centre

- Polyamide 6 wheel body, with ball bearing centre
- Tread 95 Shore A polyurethane with rounded edges
- High load capacities
- Low abrasion, non-marking, low rolling resistance
- Excellent chemical resistance, oil and grease resistance
- Leakage resistance is <10,000 ohms



Available Bore Types



Ball Bearing

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Suitable for trolleys and machinery with medium-heavy duty loads, also in case of continuous handling. The ball bearing model is excellent for manual-mechanical handling and speed up to 6km/h. Suitable for indoor and outdoor use with frequent washing and sterilisation.

Industries



Airport/
Aerospace




Automotive




Clean Room
Laboratories

Floor Suitability


Suitable for tiles and cement-resin. Not recommended for unpaved floors or in presence of processing residues. Not suitable in presence of obstacles, even if small. They do not mark or damage fragile floors.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 60WAS CONTINUED



95 Shore A



-20° C to +70° C









80 - 200mm



150 - 500kg

WHEELS



 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
80	35	12	40	150	60WAS1001
100	35	12	40	200	60WAS1002
125	40	15	50	250	60WAS1003
160	45	20	60	380	60WAS1004
200	50	20	60	500	60WAS1005