

SERIES 62GH



75 Shore A



-20° C to +70° C



200 - 400mm



800 - 1700kg

'TR Roll' polyurethane wheels with cast iron centre

- Excellent rolling resistance and elasticity highly resistant to wear and tear
- Heavy duty loads
- Mechanical handling applications
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22883:2004



Available Bore Types



Ball Bearing



Ball Bearing Facility

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Innovative product, which combines an excellent rolling resistant with the ability to damp down vibrations, overcome obstacles and very good performance and durability in case of heavy usages and mechanical handling at speeds up to 16km/h.

Industries



Airport/
Aerospace




Automotive




Towing/
Mechanical
Handling

Floor Suitability


Suitable for all types of industrial floors, even outdoors. Facilitates the overcoming of obstacles. It does not damage the floors.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 62GH CONTINUED



70 Shore A



-20°C to +70°C



200 - 400mm



800 - 1700kg















WHEELS



Ball Bearing



Ball Bearing Facility













													
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(daN)	(daN)	(daN)	(daN)	(kg)	(code)	(kg)	(code)
200	50	20	55	47	14	1000	700	800	800	3.40	622126	3.17	624126
200	80	25	88	62	18	1200	750	900	900	6.63	622136	6.14	624136
250	80	25	86	62	17	1600	800	1200	1200	8.50	622127	8.00	624127
300	80	30	86	62	17	1900	850	1400	1400	11.50	622128	11.00	624128
400	100	40	100	80	18	2000	900	1700	1700	33.50	622109	32.70	624109



Ball Bearing
















Wheel lacquer

Water resistant lacquer has been applied to the wheel and the aluminium centre. This provides protection for the wheel, when used in environments where water is present. It can extend the life of the wheel by as much as 75%.


											
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(daN)	(daN)	(daN)	(kg)	(code)	(code)
250	80	25	86	62	17	1600	800	1200	8.50	622127LQ	622127LQ
300	80	30	86	62	17	1900	850	1400	11.50	622128LQ	622128LQ
400	100	40	100	80	18	2000	900	1700	33.50	622109LQ	622109LQ



HEAVY DUTY TOWING CASTORS - PT

															
	200	50	250	140x110	105x80	11	70	126	800	5.80	627646	5.42	628656	6.35	627246

OPTIONS AVAILABLE TO ORDER



SERIES 62GH CONTINUED



70 Shore A



-20°C to +70°C



200 - 400mm



800 - 1700kg

ELECTRO WELDED CASTORS - EE MHD



											SWIVEL		FIXED		SWIVEL & BRAKE
200	50	252	135x110	105x80	11	70	157	800	6.54	628316	5.56	628416	7.42	628616	

ELECTRO WELDED SPRUNG-LOADED CASTORS EES MHD



										SWIVEL		FIXED		SWIVEL & BRAKE
200	50	268	135x110	105x80	11	65	265	800	9.22	625706	7.97	625806	10.33	626006

ELECTRO WELDED CASTORS - EE HD





										SWIVEL		FIXED		SWIVEL & BRAKE
200	80	275	175x140	140x105	14.5	65	166	900	13.1	628706	11.56	628806	13.98	628906
250	80	320	175x140	140x105	14.5	74	166	1200	15.19	628708	13.6	628808	16.07	628908
300	80	360	175x140	140x105	14.5	81	166	1400	18.31	628718	16.69	628818	19.19	628918

ELECTRO WELDED CASTORS - EE EHD



										SWIVEL		FIXED
400	100	475	250x200	210x160	19	95	1700	49.55	628729	44.85	628829	

OPTIONS AVAILABLE TO ORDER



For technical help and advice contact
T: 01457 837772 E: sales@aut.co.uk