

# SERIES 62SH



95 Shore A



-20°C to +60°C



125 - 200mm



300 - 500kg

Special hybrid wheel, soft polyurethane core, with harder polyurethane tyre

- Excellent start up coefficient due to harder, round profile tyre
- Shock absorbing soft core, thanks to soft, green, elastic polyurethane core
- Manual or mechanical handling
- Indoor or outdoor applications



## Available Bore Types



Ball Bearing

## Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

## Uses

The round profile reduces the start-up coefficient when the castors are positioned at 90° from the line of movement. Therefore it greatly reduces the amount of effort required by the operators when handling trolleys. Combined with appropriate brackets, they guarantee excellent performance for mechanical handling up to 16km/h.

## Industries



Airport/  
Aerospace



Automotive




Conveyors &  
Production




Towing/Mechanical  
Handling

## Floor Suitability


Suitable for all types of industrial floors, even outdoors. Facilitates the overcoming of obstacles. It does not damage the floors.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

# SERIES 62SH CONTINUED



95 Shore A



-20°C to +60°C



125 - 200mm









300 - 500kg

## WHEELS













Ball Bearing

 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
125	50	60	20	300	62CA125B1021
160	50	60	20	400	62CA160B1021
200	50	60	20	500	62CA200B1021











## CASTORS WITH PRESSED HOUSINGS



									 kg	SWIVEL	FIXED	SWIVEL & BRAKE
	125	50	170	135x110	105x84/76	11	50	117.5	300	62CA125B2Z21	62CA125B3Z21	62CA125B4Z21
160	50	202	135x110	105x84/76	11	57	135	400	62CA160B2Z21	62CA160B3Z21	62CA160B4Z21	
200	50	245	135x110	105x84/76	11	59	155	500	62CA200B2Z21	62CA200B3Z21	62CA200B4Z21	

## CASTORS WITH WELDED HOUSINGS



									 kg	SWIVEL	FIXED	SWIVEL & BRAKE
	125	50	170	135x110	105x84/76	11	50	117.5	300	62CA125B2Z31	62CA125B3Z31	62CA125B4Z31
160	50	202	135x110	105x84/76	11	57	135	400	62CA160B2Z31	62CA160B3Z31	62CA160B4Z31	
200	50	245	135x110	105x84/76	11	59	155	500	62CA200B2Z31	62CA200B3Z31	62CA200B4Z31	