# SERIES 68FSR



## Levelling castor with nylon wheel

- Castor with an ivory coloured, powder coated body and nylon
  wheel assembled with aluminium and ductile iron housings
- Rectangular top plate and a female thread option for attachment
- Castor is levelled by an integral nylon hand wheel on sizes 42, 50, 63 and 72mm and with a steel hexagonal nut on the heavier duty 72 and 92mm
- Levelling footpad is die-cast aluminium covered in rubber on sizes 42, 50, 63 and 72 and can lock the castor to the floor as well as act as an anti-vibration mount
- On the heavy duty sizes 72 and 92mm, the levelling pad is made from cast ductile iron. The 92mm wheel is blue in colour
- This product is both a castor and a foot mount so it can be used to move all types of equipment in factory and office environments where it is necessary to totally immobilise the equipment whilst in use or storage
- The capacities stated are for mobile use however higher capacities can be achieved with castors in static mode

#### **Available Bore Types**





#### **Environments of Use**

•	Weak Acids	•	Weak Bases
٠	Strong Acids	•	Strong Bases
٠	Water	•	Hydrocarbons
٠	Alcohol	•	Solvents

#### Uses


Intended mainly for static uses, for mediumheavy capacities. The excellent rolling resistance ensures that minimum effort is needed in handling, but only on smooth floors.



Conveyors & Production

#### **Floor Suitability**

Suitable for tiles and cement-resin. Not recommended on unpaved floors or in the presence of processing residues. They facilitate overcoming small obstacles along the path. They do not mark or damage fragile floors.



For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

# SERIES 68FSR continued



0°C 42 - 92mm

40 - 1200kg

kg



### TOP PLATE & BOLT HOLE SWIVEL CASTORS

=	Ø							Ŧ	4 km/h	SWIVEL
	50	22	83	73x73	58x58	6.5	-	60	200	68FSR0020
	63	29	102	90x90	70x70	9	-	83.5	400	68FSR0011
	72	31	120	95x95	70x70	11	-	90	700	68FSR0031
	72	31	121	95x95	70x70	11	-	89.5	900	68FSR0051
	92	54	130	100x100	70x70	13	-	115	1200	68FSR0002
	42	18	71	-	-	-	8	50	40	68FSR0000
	50	25	83	-	-	-	12	60	200	68FSR0010
	63	33	102	-	-	-	12	83.5	400	68FSR0021
	72	34	120	-	-	-	16	90	700	68FSR0041
	72	34	121	-	-	-	16	89.5	900	68FSR0061