

SERIES 68HD



70 Shore D



-30°C to +80°C



80 - 400mm



1000 - 12000kg

Polyamide 6 solid wheel, ball bearing

- Natural colour cast nylon wheel. Extra heavy duty loads
- Manual handling applications. Low rolling resistance for use on compact floors e.g. cement, epoxy resins etc
- Good resistance to many chemicals in diluted form. Plain bore wheels available on application
- Available with castors on application
- Other dimensions available, please ask us. Available in black on request



Available Bore Types



Ball Bearing

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Intended mainly for static uses, for medium-heavy capacities. The excellent rolling resistance ensures that minimum effort is needed in handling, but only on smooth floors.


Industries




Cranes & Gantries

Floor Suitability


Suitable for tiles and cement-resin. Not recommended on unpaved floors or in the presence of processing residues. They facilitate overcoming small obstacles along the path. They do not mark or damage fragile floors.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 68HD CONTINUED



70 Shore D



-30°C to +80°C









80 - 400mm



1000 - 12000kg

WHEELS



 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
80	40	20	45	1000	68HD01
100	50	20	60	1400	68HD02
125	50	20	60	1700	68HD03
150	50	30	60	2100	68HD04
150	80	50	90	3000	68HD24
160	50	30	60	2250	68HD14
200	50	35	60	2800	68HD06
200	80	50	90	4500	68HD16
250	50	40	60	3500	68HD08
250	80	50	90	4500	68HD18
300	110	70	120	10000	68HD19
400	110	80	120	12000	68HD29