

SERIES 77



95 Shore A



-20°C to +80°C



82 - 85mm



450 - 600kg

'TR' polyurethane pallet truck rollers with polyamide 6 centre

- Excellent rolling resistance and elasticity features, highly resistant to wear
- Heavy duty loads
- Manual handling applications
- Suitable for use on manual and electric pallet trucks with speeds up to 6km/h
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22883:2004



Available Bore Types



Ball Bearing



Ball Bearing Facility

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Suitable for use on manual and electric pallet trucks, with speed up to 6km/h. Their excellent values of rolling resistance make the manual handling of heavy loads easier.


Industries




Pallet Trucks

Floor Suitability


Suitable for tiles and cement-resin. Not suitable if voluminous obstacles are present.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 77 CONTINUED



95 Shore A



-20°C to +80°C



82 - 85mm



450 - 600kg














LOAD ROLLERS



Ball Bearing



Ball Bearing Facility

 (mm)	 (mm)	 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (daN)	 (daN)	 (kg)	 (code)	 (kg)	 (code)
82	70	20	70	47	14	550	300	450	0.60	772132	0.36	774132
82	90	20	90	47	14	610	340	540	0.70	772135	0.46	774135
82	100	20	100	47	14	700	380	600	0.76	772137	0.52	774137
85	70	20	70	47	14	600	310	500	0.65	772122	0.41	774122
85	90	20	90	47	14	700	350	600	0.76	772125	0.52	774125

OPTIONS AVAILABLE TO ORDER

