SERIES VG







100 - 125mn



250 - 300k

Grey elastic rubber tyre bonded to aluminium wheel centres & castors

- Aluminium centre wheel with grey elastic rubber tread
- Pressed steel, zinc plated castor body
- Without threadguards
- Ideal for handling trolleys



Available Bore Types



Ball Bearing

Environments of Use

Weak AcidsStrong Acids

Weak Bases
Strong Bases

Water
Alcohol

HydrocarbonsSolvents

Uses

Wheels with excellent elasticity features, they are particularly suitable for use on uneven surfaces, in presence of obstacles or for mixed indoor/outdoor uses with medium-duty loads. The good elasticity and rolling resistance guarantee minimum effort, particularly on uneven surfaces.

Industries







Airport/ Aerospace

Gantries


Conveyors 8

Floor Suitability

They are suitable for use on all types of floors, even in presence of obstacles. They do not mark or damage fragile floors.



Cement-Resin











With Obstacles

Not Paved

Expanded Metal

SERIES VG CONTINUED









250 - 300ks

WHEELS





Ball Bearing

	-			4 km/h	0
(mm)	(mm)	(mm)	(mm)	(daN)	(code)
100	40	12	40	250	VG100B1051
125	40	15	50	300	VG125B1051

TOP PLATE CASTORS







<u> </u>				-0-		0 0		0 0		4 km/h	SWIVEL	FIXED	SWIVEL & BRAKE
	100	40	12	40	128	105x80	80/77x60	9	40	200	VG100B2Z51	VG100B3Z51	VG100B4Z51
	100	40	12	40	128	135x110	105x84/76	11	40	200	VG100B2Z52	VG100B3Z52	VG100B4Z52
	125	40	15	50	155	105x80	80/77x60	9	40	250	VG125B2Z51	VG125B3Z51	VG125B4Z51
	125	40	15	50	155	135x110	105x84/76	11	40	250	VG125B2Z52	VG125B3Z52	VG125B4Z52